

SOLTEX, INC.

3707 FM 1960 West, Suite 560

Houston, TX 77068

Phone: 281-587-0900 Fax: 281-587-1998

www.soltexinc.com

MATERIAL SAFETY DATA SHEET

Page 1 of 4

PRODUCT INFORMATION

Product Name: Synthetic Alkylate Fluid ISO 22, ISO 32, ISO 46,
ISO 68, ISO 100

Chemical Name: Alkylate

CAS NO.: 68855-24-3

Emergency Phone Number: CHEMTREC (800) 424-9300

Other Safety Information: (281) 587-0900

Exposure Standard: No OSHA standard or Threshold Limit Value
has been established for this material.

HMIS/NFPA Codes: (Health;0)(Flammibility;1)(Reactivity;0)

DOT Proper Shipping Name: Not Regulated

TYPICAL CHEMICAL & PHYSICAL PROPERTIES

Specific Gravity: 0.86 **Viscosity:** 19-105 @ 40 Deg. C

Boiling Point: 315 Deg. C **Vapor Pressure:** N/A

Solubility in Water: Insoluble in water.

REACTIVITY DATA

Stability: Stable.

Hazardous Decomposition Products: None. Normal combustion forms carbon dioxide
and water vapor; incomplete combustion
can produce carbon monoxide.

Hazardous Polymerization: Will not occur.

SOLTEX, INC.

3707 FM 1960 West, Suite 560

Houston, TX 77068

Phone: 281-587-0900 Fax: 281-587-1998

www.soltexinc.com

MSDS Page 2 of 4

HEALTH INFORMATION & PROTECTION

NATURE OF HAZARD

EYE CONTACT:

Slightly irritating but does not injure eye tissue.

SKIN CONTACT:

No hazard in normal industrial use. Prolonged contact may cause irritation.

Exposure to hot material may cause thermal burns.

INHALATION:

Negligible hazard at ambient (-18 to 38 Deg. C; 0 to 100 Deg. F) or recommended blending temperature.

Avoid breathing vapors or mists.

INGESTION:

Minimal toxicity. Give water. Do not induce vomiting.

FIRST AID

EYE CONTACT:

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

INHALATION:

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION:

First aid is normally not required.

WORKPLACE EXPOSURE LIMITS

THE FOLLOWING OCCUPATIONAL EXPOSURE LIMITS ARE RECOMMENDED:

Due to the oil-based components of this mixture, if misting occurs, control of exposure to 5mg/m³ or less is recommended.

SOLTEX, INC.

3707 FM 1960 West, Suite 560

Houston, TX 77068

Phone: 281-587-0900 Fax: 281-587-1998

www.soltexinc.com

MSDS Page 3 of 4

HEALTH INFORMATION & PROTECTION - CONTINUED

PRECAUTIONS

PERSONAL PROTECTION:

For open systems where contact is likely, wear safety glasses with side shields.

Where contact may occur, wear safety glasses with side shields.

Where contact may occur with hot materials, wear thermal resistant gloves, arm protection and a face shield.

Where concentrations in air may exceed the limits given in this section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION:

The use of mechanical dilution ventilation is recommended whenever this product is used in confined space, is heated above ambient temperatures, or is agitated.

FIRE AND EXPLOSION DATA

Flash Point: 150eg. C min.

Flammable Limits: N/A

Extinguishing Media: CO₂, Dry Chemical, Foam, or any Class B agent.

Fire Fighting: Firefighters or others exposed to vapors or products of combustion should wear full protective clothing and self-contained breathing apparatus. Thoroughly decontaminate equipment after use.

STORAGE AND ENVIRONMENTAL PROTECTION

STORAGE REQUIREMENTS:

No special requirements

SPILLS AND LEAKS:

Remove mechanically or contain on an absorbent material. Treat as an oil spill.

SOLTEX, INC.

3707 FM 1960 West, Suite 560

Houston, TX 77068

Phone: 281-587-0900 Fax: 281-587-1998

www.soltexinc.com

MSDS Page 4 of 4

STORAGE AND ENVIRONMENTAL PROTECTION - CONTINUED

WASTE DISPOSAL:

Disposal must be in accordance with applicable federal, state, or local regulations. Determine waste classification at time of disposal. Conditions of use may render the spent product a hazardous waste. Enclosed-controlled incineration is recommended unless directed otherwise by applicable ordinances.

EMPTY CONTAINERS:

The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture or weld on or near this container. Since the emptied containers retain product residue, follow label warnings even after container is emptied.

REGULATORY INFORMATION

TSCA Status:

This product is listed on the TSCA inventory.

CERCLA Reportable Quantity:

This product is not subject of any special reporting under the requirements under 40 CFR Part 302.4.

SARA Status:

This product does not contain any Section 313 reportable ingredients and is not regulated under SARA Title III.

OSHA Hazard Communication Standard:

This product is not hazardous as defined in 29 CFR 1910.1200.

DOT Hazard Class/ID Number:

Not applicable.

Revision Date: 02/09

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation, or authorization given or implied to practice any patented invention without a valid license. The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet.