

## Electrifill 2288

### 1. Identification of the Substance/Preparation and the Company/Undertaking

Product Name: Electrifiill 2288

Product Type: Insulating mineral oil

Supplier: SOLTEX, INC.  
3707 FM1960 WEST, SUITE 560  
HOUSTON, TX 77068  
USA

**Emergency Phone Number: CHEMTREC (800) 424-9300**  
**Other Safety Information: (281) 587-0900**

### 2. Hazards identification

- Classification: No classification needed according to 67/548/EC and 1999/45/EC.
- Human Health: Inhalation of vapors and/or mists might irritate respiratory tract.
- Prolonged skin contact will cause defatting and possible irritation.
- Eye contact might cause irritation.
- Environment: Slow biodegradation, the product will remain for a long time in the environment. It is a risk for contamination of earth, soil and water.
- Physical and chemical hazard: At elevated temperatures, flammable vapors and decomposition products will be released. It is a risk for slippery floors if spilled out.

### 3. Composition/Information of Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>EC-No</u>	<u>Weight-%</u>
Hydrotreated Light Naphthenic distillate	64742-53-6	265-156-6	>99.0%
2,6-ditertiary Butyl-4-Methyl Phenol	128-37-0	204-881-4	<0.1%

### 4. First Aid Measures

General advice:

- Inhalation: If inhalation of mists, fumes, or vapors occurs causing irritation, move to fresh air. If the symptoms persist, obtain medical advice.
- Skin contact: Remove immediately adhering matter and wash off with soap and plenty of water.
- Eye contact: Rinse with plenty of water.
- Ingestion: Clean mouth with water. Obtain medical advice if a large amount has been swallowed. Do not induce vomiting.

## **5. Fire-fighting Measures**

Suitable extinguishing media:

- Extinguish preferably with dry chemical, carbon dioxide (CO<sub>2</sub>), or foam. Water-spray/mist may be used.

Extinguishing media which must not be used for safety reasons:

- Water jet, unless used by authorized people.

## **6. Accidental Release Measures**

- Personal precautions: Suitable protection equipment should be used. In case of large spillage, the cleaning procedure should be carried out using suitable protective clothing such as overalls, gloves and boots. Remove contaminated clothes as soon as possible. Smaller spillage can be wiped up with paper cloths, using protective gloves.
- Environmental precautions: Prevent spills from spreading to drains, sewers, watercourses, and soil. Contact local safety authorities.
- Methods for cleaning up: Absorb leaking product with sand, earth or other suitable inert material and collect. Disposal according to section 13.

## **7. Handling and Storage**

- Handling: Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high-speed mechanical equipment, vapors or mists might be released and require a well-ventilated workplace.
- Storage: Store at ambient temperature or with lowest necessary heating as handling requires.

## **8. Exposure Controls/Personal Protection**

Control parameters: Exposure via the air and normal handling.

- Chemical name: Mineral oil.
- Short-term value: 5 mg/m<sup>3</sup>. TLV-TWA 8 hours ACGIH (1998).
- Engineering measures to reduce exposure: Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.

Personal protection equipment:

- Respiratory protection: If the product is heated under manual handling, use suitable mask with filter A1P2 or A2P2. Handling in automatic production lines, with exhaust or ventilation, will not require mask.
- Hand protection: Wear oil-resistant protective gloves if there is a risk of repeated skin contact. Suitable gloves are neoprene, nitrile, acrylonitrilebutadiene rubber, or PVC. Take notice of CEN 420:94, CEN 374:1-3:94 and CEN 388:94.
- Eye protection: Wear safety goggles/safe shield if splashes may occur.
- Skin and body protection: Wear protective clothing if there is a risk of skin contact and change them frequently, or when contaminated.
- Hygienic measures: Act in accordance with good industrial hygiene and safety practice.

**MATERIAL SAFETY DATA SHEET****9. Physical and Chemical Properties**

Form:	Viscous liquid
Color:	<0.5 pale light yellow
Odor:	Odorless / light petroleum
Pour point:	-40°C
Initial boiling point:	>250°C
Specific Gravity 15°C:	0.87
Flash point, PM:	130°C
Auto ignition temp.:	>270°C
Solubility in water:	Non soluble
Solubility in organic solvents:	Soluble
Decomposition temp.:	>280°C
Vapor pressure at 100°C:	<0.5 mm Hg
DMSO extractible compounds according to IP346:	< 3%
Calculated partition coefficient n-octanol/water, log Pow:	>6
Viscosity at 40°C:	9 - 11 cSt
pH:	non relevant

**10. Stability and Reactivity**

- Stability: Stable at normal conditions. Starts to decompose above 280°C
- Avoid: Excessive heating and highly oxidizing agents.
- Hazardous decomposition products: Flammable gases which might also be noxious. With air present, there is a risk for auto ignition at temperatures >270°C.

**11. Toxicological Information**

## Acute toxicity:

- Studies available indicate oral and dermal LD<sub>50</sub> of >5,000 mg/kg which is considered as low acute toxicity.

## Local effects:

- Inhalation: Prolonged and repeated inhalation of mist or vapor generated at elevated temperatures may irritate respiratory tract.
- Oral: May cause nausea and eventually vomiting and diarrhea.
- Skin contact: Prolonged or repeated exposure may lead to defatting of the skin and subsequent irritation.
- Eye contact: May cause redness and transient pain.
- Sensitization: Studies indicate no evidence of sensitization.

## 12. Ecological Information

- Mobility: Low, due to low water solubility.
- Persistence/degradability: The base oil is not readily biodegradable. Substances may not meet criteria for ready biodegradability. Studies indicate inherent, primary biodegradation in the range of 20-60 % based on carbon dioxide evolution.
- Bio-accumulation: Base oil has Log Pow in the range >3.9->6.0.
- Log Pow is used for estimating the bioaccumulation in fish. A value >3.0 indicates possible bioaccumulation. The size of the hydrocarbon molecules reduces the risk for bioaccumulation.
- Ecotoxicity: Aquatic toxicity data on base oils indicate LC50 values of >1,000 mg/l, which is considered as low toxicity. Chronic toxicity studies shows no long-term hazard to the aquatic environment.

## 13. Disposal Considerations

- Residues of unused product are not regarded as hazardous waste. Residues of products/packaging must not be disposed of in the environment, but taken care of in accordance with local regulations.
- Emptying instructions:
- Drums: Turn the drum upside down and tilt it approximately 10° until nondripping. Nondripping is less than one drop / minute at 15 °C. The product viscosity depends on temperature, and it is important that the emptying is not done at too low of a temperature. It may be necessary to scrape out high viscous products. When the drum is nondripping, send it for recycling. If the residue volume is more than 1%, send it for destruction of drums. Empty drums with < 1 % residue are not dangerous goods. Refer to local regulations.
  - Bags for one way use/multiple use: Follow instructions given by the bag manufacturer. The last residues in the bag can be removed by placing the hose over the remaining residues or by lifting the bag so the product can run towards the hose.
  - Bottom residues: Roll up the bag towards the hose to press out the oil.
  - One way bags of polyethylene can be recycled or disposed of by incineration. Refer to local regulations.

## 14. Transport Information

The product is not classified as hazardous goods for land, sea, and air transport according to the respective regulations (ADR, IMDG, IATA-DGR).

## 15. Regulatory Information

- Classified according to European directives on classification of hazardous substances and preparations. Not classified as hazardous. No statutory label required.
- Listed in TSCA ( Toxic Substances Control Act) and EINECS.
- Listed in Canadian DSL registry.

**16. Other Information**

The information for labeling and ecotoxicity is according to Concawe Report No. 95/59, 98/54, 05/6 and 01/54.

Classified according to the Dangerous Substance Directive, 67/548/EC up to the most recent ATP, the Dangerous Preparation Directive 1999/45/EC, and the Safety Data Sheet Directive 2001/58/EC, and REACH (EC) No 1907/2006 according to transitional provisions.

Classification of component with CAS no 128-37-0:

- Classified as dangerous for the environment, N, according to 67/548/EC and 1999/45/EC.
- R51/53: Toxic to aquatic organisms, may cause long- term effects in the aquatic environment.  
Component CAS no 64742-53-6 has DMSO extractible compounds according to IP 346 <3%.

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 w%w DMSO extract as measured by IP 346.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

**Date: 8/30/11**

**Page 5 of 5**