

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT INFORMATION

SUPPLIER: Soltex, Inc.
3707 FM1960 West, Suite 560
Houston, TX 77068

EMERGENCY TELEPHONE NUMBERS:
Business Hours: 8:30a.m. - 5:00p.m. - (281) 587 0900 (USA)
After Hours: (281) 543-4155
CANUTEC: (613) 996-6666
CHEMTREC: 1-800-424-9300

Hazardous Material Identification System

Health	[0]
Flammability	[1]
Reactivity	[0]
Personal Protection	[A]
WHMIS Rating	[N/A]
WHMIS Controlled or Uncontrolled Product (C/U)	[U]

MANUFACTURER: IGI Baytown, TX	PRODUCT CODE # Naptel 510
MATERIAL NAME: Naptel 510 Flooding Compound	
MATERIAL USE: Telecom Cable Flooding Compound	

SECTION II - HAZARDOUS INGREDIENTS

Hazardous Ingredients	Conc. % Wt/Wt	Toxicity Data LD ₅₀ /LC ₅₀	C.A.S. #
Polymeric hindered Phenolic Antioxidant	0.15 - 0.30	Not available	Not available
1,11-(3,6,9- Trioxaudecyl) bis- 3-(dodecylthio) propionate Antioxidant	0.05 - 0.15	Not available	Not available

SECTION III - PHYSICAL DATA

Physical State: Gas [] Liquid [] Solid [X]

Odour and Appearance: Odourless, Pale Brown Amorphous Waxy Solid

Odour Threshold (p.p.m.): NOT AVAILABLE

Vapour Pressure (mm Hg): NOT AVAILABLE

pH: NOT AVAILABLE

Density/25°C: 0.890 Kg-Litre Typical

Vapour Density (Air = 1): NOT APPLICABLE AT AMBIENT TEMPERATURE

Evaporation Rate (n butyl acetate = 1): NOT APPLICABLE AT AMBIENT TEMPERATURE

Coefficient Of Water/Oil Distribution: NOT AVAILABLE

Boiling Point (760 mmHg): NOT AVAILABLE

Viscosity (150°C) ASTM3236: 180 cps Typical

Softening Point (R and B, ASTM – E28) 115°C Typical

SECTION IV - FIRE OR EXPLOSION HAZARD

Flammability: If yes, under which conditions: AT TEMPERATURES GREATER THAN TYPICALLY 235°C WHEN EXPOSED TO SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION.
Yes [X] No []

Means of Extinction: CO₂, FOAM, DRY CHEMICAL.

Upper Flammability Limit: NOT AVAILABLE

Lower Flammability Limit: NOT AVAILABLE

Auto Ignition Temperature: NOT AVAILABLE

SECTION IV - FIRE OR EXPLOSION HAZARD (CONTINUED)

Hazardous Combustion Products: CO, CO₂

Flash Point (ASTM D92): 235°C TYPICAL

Explosion Data - Sensitivity to:

1) Mechanical Impact: NIL

2) Static Discharge: NIL

SECTION V - REACTIVITY DATA

Chemical Stability: If no, under which conditions:
Stable NOT APPLICABLE
Unstable

Incompatibility To Other Substances: If so, which ones:
Yes No STRONG OXIDIZING AGENTS

Reactivity and under what conditions: NOT APPLICABLE

Hazardous Decomposition Products: NOT APPLICABLE

SECTION VI - TOXICOLOGICAL PROPERTIES

Route of Entry:

1) Skin Contact: MAY CAUSE MILD DERMATITIS ON PROLONGED CONTACT WITH SENSITIVE OR ALLERGIC PEOPLE

2) Eye Contact: MINIMAL IRRITATION MAY OCCUR

3) Ingestion: CONSIDERED TO BE NON TOXIC

4) Skin Absorption: CONSIDERED TO BE NON TOXIC

5) Inhalation: NOT APPLICABLE AT AMBIENT TEMPERATURE. ABOVE 100°C VAPOUR MAY CAUSE HEADACHE AND/OR NAUSEA.

Toxicologically Synergistic Materials: NONE KNOWN

Effects of Acute Exposure to Material: NOT APPLICABLE

Effects of Chronic Exposure to Material: MAY CAUSE MILD DERMATITIS TO SENSITIVE OR ALLERGIC PEOPLE

Exposure Limit: NOT DETERMINED

Irritancy of Material: NOT APPLICABLE

Sensitization to Material: NOT APPLICABLE

Teratogenicity: NOT APPLICABLE

Carcinogenicity: NOT APPLICABLE

Mutagenicity: NOT APPLICABLE

Reproductive Effects: NOT APPLICABLE

SECTION VII - PREVENTATIVE MEASURES

Personal Protective Equipment:
SAFETY GLASSES AT AMBIENT TEMPERATURE

Engineering Controls (eg. ventilation, enclosed process, specify):

SECTION VII - PREVENTATIVE MEASURES (CONTINUED)

NONE REQUIRED AT AMBIENT TEMPERATURE. LOCAL VENTILATION RECOMMENDED WHEN HANDLING AT 100°C AND ABOVE

Leak and Spill Procedure:
CONTAIN LIQUID BY DYKING UNTIL SOLIDIFICATION OCCURS, SCRAPE UP, PLACE IN CONTAINER.
Waste Disposal:
RECLAIM. DISPOSE OF BY LICENSED AND RECOGNIZED OPERATOR.

Storage and Handling Procedures:
STORE AWAY FROM EXCESSIVE HEAT.

Special Shipping Requirements:
No special shipping requirement

Other Regulatory Controls:

SARA/TITLE III - TOXIC CHEMICALS LIST
THIS PRODUCT DOES NOT CONTAIN A TOXIC CHEMICAL FOR ROUTINE ANNUAL "TOXIC CHEMICAL RELEASE REPORTING" UNDER SEC. 313 (40 CFR 372).

TSCA INVENTORY STATUS: CHEMICAL COMPONENTS LISTED ON TSCA INVENTORY

DOMESTIC SUBSTANCE LIST: CHEMICAL COMPONENTS LIST ON THE DSL

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):
THIS PRODUCT DOES NOT CONTAIN A CHEMICAL KNOWN TO THE STATE TO CAUSE CANCER OR REPRODUCTIVE TOXICITY.

NEW JERSEY RIGHT TO KNOW LABELING INFORMATION:

Butene, homopolymer	CAS 9003-29-6
Ethene, Homopolymer	CAS 9002-88-4
Polymeric hindered Phenolic Antioxidant	CAS not available
1,11-(3,6,9- Trioxaudecyl) bis- 3-(dodecylthio) propionate Antioxidant	CAS not available

SECTION VIII - FIRST AID MEASURES

Specific First Aid Measures:

SKIN CONTACT: WASH WITH MILD SOAP AND WATER. LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE.
EYE CONTACT: FLUSH WITH COPIOUS QUANTITIES OF WATER FOR AT LEAST 15 MINUTES.
INGESTION: OBTAIN MEDICAL ATTENTION.
INHALATION: REMOVE TO FRESH AIR.

SECTION IX - SPECIAL NOTES

THIS MSDS REVISION HAS CHANGES IN THE FOLLOWING SECTIONS:

SECTION I - PRODUCT INFORMATION: Supplier Name
SECTION X - PREPARATION INFORMATION: Supplier Name, Date, Revision Number, Preparation Info. Address, Phone Number

SECTION X - PREPARATION INFORMATION

Prepared by: TECHNICAL DEPT.
Soltex, Inc.
3707 FM1960 West, Suite 560 Houston, TX 77068

Phone Number: 281 587 0900
Date: February 6, 2006; Revision Number (#3)

The company shall not be liable for any damages arising from the information contained on this data sheet howsoever caused, if the product in question is not employed in normal or reasonably foreseeable use or circumstances. The company shall not be liable for any indirect or consequential damages arising out of the use of the information contained on this data sheet howsoever caused.
