

MATERIAL SAFETY DATA SHEET

Page 1 of 4

PRODUCT INFORMATION

Product Name: PCA 9055
Chemical Name: Amine Detergent Package
Emergency Phone Number: CHEMTREC (800) 424-9300
Other Safety Information: (281) 587-0900
Exposure Standard: No OSHA standard or Threshold Limit Value has been established for this material.
HMIS/NFPA CODES: (Health;2)(Flammability;2)(Reactivity;0)
DOT Proper Shipping Name: Flammable liquids, n.o.s. (xylene, petroleum distillates)

TYPICAL CHEMICAL & PHYSICAL PROPERTIES

Specific Gravity: 0.905 typical **Viscosity:** 65 – 75 cSt @ 100 deg. C
Boiling Point: N/A **Solubility in Water:** Negligible

REACTIVITY DATA

Stability: Stable.
Materials to avoid: Strong oxidizing and reducing agents
Hazardous Decomposition Products: Oxides of carbon and nitrogen.
Hazardous Polymerization: Will not occur.

HEALTH INFORMATION & PROTECTION

NATURE OF HAZARD

EYE CONTACT:
Expected to be an eye irritant.
SKIN CONTACT:
Expected to be a skin irritant.



SOLTEX
3707 FM 1960 West, Suite 560
Houston, TX 77068
281-587-0900 Fax: 281-587-1998
www.soltexinc.com

MSDS Page 2 of 4

INHALATION:

Avoid breathing vapors or mists.

Expected to be irritating to respiratory tract. Symptoms of overexposure to vapors include drowsiness, weakness, headache, dizziness and nausea.

INGESTION:

Aspiration is expected to cause lung injury.

FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water for at least 15 minutes or until irritation subsides. If irritation persists, get medical attention.

INHALATION:

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION:

If swallowed, give 2 glasses of water. Do not induce vomiting. If vomiting occurs naturally, have victim lean over to avoid aspiration. Seek medical advice.

WORKPLACE EXPOSURE LIMITS

THE FOLLOWING OCCUPATIONAL EXPOSURE LIMITS ARE RECOMMENDED:

Not established for this mixture. See Composition information on ingredients.

PRECAUTIONS

PERSONAL PROTECTION:

For open systems where contact is likely, wear safety glasses with side shields.

Where contact may occur, wear safety glasses with side shields.

Where contact may occur with hot materials, wear thermal resistant gloves, arm protection and a face shield.

Where concentrations in air may exceed the limits given in this section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION:

The use of mechanical dilution ventilation is recommended whenever this product is used in confined space, is heated above ambient temperatures, or is agitated.



SOLTEX
3707 FM 1960 West, Suite 560
Houston, TX 77068
281-587-0900 Fax: 281-587-1998
www.soltexinc.com

MSDS Page 3 of 4

FIRE AND EXPLOSION DATA

Flash Point: 95 °C min. PMCC

Flammable Limits: N/A

Extinguishing Media: CO₂, dry chemical, water spray (fog), or foam.

Fire Fighting: Firefighters or others exposed to vapors or products of combustion should wear full protective clothing and self-contained breathing apparatus. Thoroughly decontaminate equipment after use.

STORAGE AND ENVIRONMENTAL PROTECTION

STORAGE REQUIREMENTS:

Store containers in cool, dry, well-ventilated area away from sources of ignition. Keep containers closed when not in use. Ground all containers when transferring contents.

SPILLS AND LEAKS:

Remove mechanically or contain on an absorbent material. Treat as an oil spill.

WASTE DISPOSAL:

Disposal must be in accordance with applicable federal, state, or local regulations. Determine waste classification at time of disposal. Conditions of use may render the spent product a hazardous waste. Enclosed-controlled incineration is recommended unless directed otherwise by applicable ordinances.

EMPTY CONTAINERS:

The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture or weld on or near this container. Since the emptied containers retain product residue, follow label warnings even after container is emptied.

REGULATORY INFORMATION

TSCA Status:

All components are listed or exempted on the TSCA inventory.

CERCLA Reportable Quantity:

Cumene RQ = 5000, Ethylbenzene RQ = 1000, Xylene RQ = 100

SARA 311/ 312 Reporting:

Health	Immediate (Acute)	Yes
Health	Delayed (Chronic)	No



SOLTEX
3707 FM 1960 West, Suite 560
Houston, TX 77068
281-587-0900 Fax: 281-587-1998
www.soltexinc.com

MSDS Page 4 of 4

Physical	Fire	Yes
Physical	Sudden Release of Pressure	No
Physical	Reactive	No
	Nuisance Mist/ Dust Only	No

Regulated Component name:

Cumene	<1.0 Wt%	SARA 313, NJ RTK & PA RTK
Ethylbenzene	< 1.0 Wt%	NJ RTK
Xylene	< 1.0 Wt%	NJ RTK
1,2, 4 – trimethylbenzene	<1.0 Wt%	SARA 313 & NJ RTK

OSHA Hazard Communication Standard:

This product is hazardous as defined in 29 CFR 1910.1200.

DOT Hazard Class/ID Number:

3 / UN1993, III

See CERLA for reportable quantity, this material is a marine pollutant

Revision Date: 12/2008

This information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.