



*Adding value to  
your formulations*

TECHNICAL DATA SHEET

## SOLTEX HCP SOLVENT

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL RESULT</u>
Viscosity, 40 °C	D-445	1.418 mm <sup>2</sup> /s
Color, Pt-Co scale	D-5386	17
Appearance	D-4176	Bright & Clear
API Gravity	D-4052	49.4°
Flash point, COC	D-92	21 °C
Water	D-6304	146 ppm

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.  
**Date: 07/01/2010**

SOLTEX, INC. 3707 FM 1960 West, Suite 560, Houston, TX 77068 | Phone: 281.587.0900 | Fax: 281.587.1998 [www.soltexinc.com](http://www.soltexinc.com)

● ACETYLENE BLACK ● ALKYLATES ● BASE OILS (GROUP II AND GROUP III) ● CABLE FLOOD, FILL AND GELS ● DIELECTRIC FLUIDS ● PERFORMANCE ADDITIVES  
● POLYALPHAOLEFINS ● POLYBUTENES (STANDARD GRADES) ● REFRIGERATION FLUIDS ● SPECIALTY POLYISOBUTYLENE ● SULFONATES