

OMG Tackifiers

Description: OMG Tackifiers are high molecular weight polymers in oil which provide lubricants with tack, adhesion, and non-drip characteristics to lubricant formulations. There are three grades available: general purpose, light colored and food grade.

Application: Typically used in bar and chain lubricants, greases, way lubricants, and rust or corrosion inhibitor packages.

Treat Rate: 0.4 to 2.0 wt % of lubricant formulations

Typical Properties			
Property	E 857	E 858	E 859 FG
Specific Gravity, ASTM D1298-99	0.866	0.866	0.865
Density, ASTM D1298-99	7.22	7.22	7.21
Flash Point (C), ASTM 93-00	210	198	210
Viscosity@ 100C, ASTM D1296-99 (cSt)	2500-4000	2500-4000	3000-4400
Color Gardner, ASTM D1544-98	1	6 max	1

Storage

& Handling: Care should be taken not to subject the material to high shear environments while blending and packaging. The polymer may become insoluble if added to a highly polar solution. Store the product in a cool, dry environment.

Packaging: Available in bulk or 55 gallon drums.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

Date: 9/14/2010