

PCA 2886 PCMO

(Engine Oil Additive Package)

Application: PCA 2886 is manufactured using state-of-the-art technology and components designed for use with API Group I and Group II base stocks to formulate high-quality motor oils meeting the requirements of ILSAC GF-4 / API SM service level. PCA 2886 has many years of field testing and performance approvals with exceptional results.

Recommended Dosages:

PCA 2886 is used to formulate mono-grade and multi-grade engine oils with a non-dispersant viscosity modifier.

API SM	9.0 Wt%	API SL	10.0 Wt%
API SJ	9.5 Wt%	API SH	9.3 Wt%
API SG	9.1 Wt%		

Typical Properties:

Typical Value

Physical:

Specific Gravity @ 15.6 °C	0.97
Pounds/ Gallon @ 60 °F	8.11
Viscosity, cSt @ 100 °C	65

Chemical:

TBN, mg KOH/g	78
Calcium, Wt%	2.00
Nitrogen, Wt%	1.10
Phosphorus, Wt%	0.87
Zinc, Wt%	0.90
Molybdenum, ppm	425

Shipping Information:

This product is not a DOT regulated material

Availability:

PCA 2886 is available in drums and in bulk (tank trucks and railcars).

Storage and Handling:

Maximum temperatures of 60 °C (140 °F) for handling and 38 °C (100 °F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product. **Date: 10/19/2010**