

PCA 9070/9073 and PCA 9080

Description: PCA 9070/9073 and PCA 9080 are ashless, chlorine free polybutenyl succinimide (PIBSI) products derived from 950 and 1300 molecular weight polybutenes, respectively, and they function as dispersants in lubricants.

Application: Typically used as dispersants in engine oils, gear oils, industrial oils and additive packages.

Benefits: Compatible with a wide range of co-additives and solvents, non-chlorine containing product, environmentally compatible and excellent dispersants..

Treat rates: 4-10 % in finished oils with suitable package or 15 to 25% in additive packages/field blends.

Property	Typical Properties			
	ASTM Method	PCA 9070	PCA 9073	PCA 9080
Specific Gravity	D-4052	0.90	0.90	0.90
Density, lb/gl	D-4052	7.5	7.5	7.5
Flash Point (C)	D -93	225	225	225
Viscosity cSt @ 100C	D-445	130	450	300
Nitrogen content, wt%	D-5762	2.2	3.2	2.0

Storage

& Handling: This product is not a DOT regulated material unless shipped at temperatures exceeding 100°C. See MSDS for details.

Packaging: Available in bulk, totes or 55 gallon drums.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

Date: 7/29/11