

## Soltac™ 922 Tackifer / Viscosity Modifier

Soltac™ 922 is a colorless and chemically inert liquid useful as a tackifier and viscosity modifier for grease production and formulations.

Soltac™ 922 is non-drying and highly resistant to oxidation. It is non-toxic and will not leave any residue when volatilized or thermally decomposed.

**Performance Benefits:**

- Compatibility with a wide range of co-additives and solvents.
- Provides excellent dispersancy and tack for producing grease.
- Formulated for ease of use / handling in drum or bulk quantities.
- Environmentally compatible.

**TYPICAL PHYSICAL PROPERTIES**

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL</u>
Color, ASTM	D1500	< 2
Viscosity, cSt @ 100 °C	D445	800 – 1,000
Viscosity, cSt @ 60 °C	D445	6,500-7,500
Viscosity, cSt @ 40 °C	D445	26,000-29,000
Viscosity Index	D-2770	> 200
Flash Point, PMCC, °C, min.	D-93	190 min
Specific Gravity	D-1298	0.90
Density, lb/gal	D-1298	7.50

**Shipping Information:**

This product is not a DOT regulated material

**Availability:**

Soltac™ 922 is available in drums and in bulk (tank trucks).  
Samples are available upon request.

**SAFETY, HANDLING AND STORAGE**

Consult the MSDS for proper handling information

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

**Date: 07/08/2010**