



*Adding value to
your formulations*

TECHNICAL DATA SHEET

SULFOL 500

PETROLEUM-TYPE NATURAL SODIUM SULFONATE WITH HIGH MOLECULAR WEIGHT. FOR COMPOUNDING EMULSIFIABLE OILS OR AS BASES, DISPERSANTS.

TECHNICAL PROPERTIES

<u>PROPERTY</u>	<u>Typical Properties</u>
SODIUM SULFONATE CONTENT, %	62
INORGANIC SALT CONTENT, %	0.6
MOISTURE CONTENT, %	4.0
OIL CONTENT, %	34
AVERAGE MOLECULAR WEIGHT	500
DENSITY, 15 °C	1.01
COLOR, ASTM (diluted to 15%)	4.5

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product. **Date: 07/06/2010**

SOLTEX, INC. 3707 FM 1960 West, Suite 560, Houston, TX 77068 | Phone: 281.587.0900 | Fax: 281.587.1998 www.soltexinc.com

● ACETYLENE BLACK ● ALKYLATES ● BASE OILS (GROUP II AND GROUP III) ● CABLE FLOOD, FILL AND GELS ● DIELECTRIC FLUIDS ● PERFORMANCE ADDITIVES
● POLYALPHAOLEFINS ● POLYBUTENES (STANDARD GRADES) ● REFRIGERATION FLUIDS ● SPECIALTY POLYISOBUTYLENE ● SULFONATES