

ThixoCal™ 2452***Water resistant Corrosion Preventive Coating Compound***

ThixoCal™ 2452 is a formulated waxy type sulfonate coating that provides excellent water resistance and salt spray protection. This product is comprised of a thixotropic calcium sulfonate, waxes, and other ingredients in a mineral spirits carrier. ThixoCal™ 2452 is an excellent candidate for rustproofing applications for automotive, truck, and military vehicles. This product provides a waxy film with some tack and offers excellent performance when immersed in water.

TYPICAL PROPERTIES (not specifications):

| <u>PROPERTY</u> | <u>ASTM</u> | <u>TYPICAL</u> |
|--------------------------|-------------|----------------|
| Non-volatiles, Wt% | D2369 | 52 min |
| Brookfield Viscosity, cP | D2196 | 5,000 – 9,000 |
| Flash Point, °F | D93 | 105 min |
| Lbs/ Gal. @ 25°C | D1475 | 7.7 |

AVAILABILITY

ThixoCal™ 2452 is available in bulk and 55 gallon drums

SAFETY, HANDLING AND STORAGE

ThixoCal™ 2452 contains mineral spirits and should be stored away from heat, flames, and sources of ignition. Prolonged breathing of vapors should be avoided. Consult MSDS for further precautions and handling advice.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

Date: 07/06/2010