

ThixoCal™ 3000A

Waxy Corrosion Preventive Compound

ThixoCal™ 3000A is a partially formulated base compound comprised of gelled calcium sulfonate, wax, oil, and other ingredients in mineral spirits. ThixoCal™ 3000A can be further formulate by incorporating additional, asphalts, resins, oils, or other ingredients. When further diluted with mineral spirits ThixoCal™ 3000A can be used as a protective coating for short term outdoor or long term indoor storage.

TECHNICAL PROPERTIES (*not specifications*):

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL</u>
Non-volatiles, Wt%	D2369	58 - 62
Brookfield Viscosity, cP	D2196	40 - 65,000
Flash Point, °F min.	D93	105
Lbs/ Gal. @ 25°C	D1475	7.8 - 8.0

AVAILABILITY

ThixoCal™ 3000A is available in drums.

SAFETY, HANDLING AND STORAGE

ThixoCal™ 3000A contains mineral spirits and should be stored away from heat, flame and sources of ignition. Prolonged breathing of vapors should be avoided. Consult MSDS for further precautions and handling advice.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product. **Date: 07/06/2010**