

ThixoCal™5000A

Formulated Waxy Corrosion Preventive Compound

ThixoCal 5000A is a dispersion of modified calcium sulfonate, waxes and other ingredients in mineral spirits. This corrosion preventive compound is typically used in vehicle rust proofing applications. It is a good choice for long term indoor storage and may be pigmented for use in long term outdoor storage applications.

TECHNICAL PROPERTIES *(not specifications):*

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL</u>
NON VOLATILE, Wt%	D2369	68 - 72
VISCOSITY, cps	D2196	45 - 85,000
FLASH POINT, °F	D93	105 min.
DENSITY @ 25°C, pounds/gallon	D1475	7.6

AVAILABILITY

ThixoCal 5000A is available in drums.

SAFETY, HANDLING, AND STORAGE

ThixoCal 5000A contains mineral spirits and should be stored away from heat, flame and sources of ignition. Prolonged breathing of vapors should be avoided. Consult MSDS for further precautions and handling advice.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product. **Date: 07/06/2010**