

ThixoCal™ 5300

High Solids, Moderately Formulated Corrosion Preventive Compound

ThixoCal™ 5300 is a moderately formulated, corrosion preventive compound that offers low VOC's and high solids. ThixoCal™ 5300 combines gelled calcium sulfonate with waxes and other film formers in a mineral spirits carrier. ThixoCal™ 5300 provides firm, tack free, waxy, dry films that exhibit excellent salt spray protection.

TECHNICAL PROPERTIES *(not specifications):*

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL</u>
Non-volatiles, Wt%	D2369	68 - 73
Brookfield Viscosity, cP	D2196	10 - 25,000
Flash Point, °F min.	D93	105
Lbs/ Gal. @ 25°C	D1475	8.3

PERFORMANCE

Salt spray performance for this product is typically in excess of 5,000 hours at 3 mils dry film thickness when tested in accordance with ASTM B-117.

AVAILABILITY

ThixoCal™ 5300 is available in drums and bulk

SAFETY, HANDLING AND STORAGE

ThixoCal™ 5300 contains mineral spirits and should be stored away from heat, flame and sources of ignition. Prolonged breathing of vapors should be avoided. Consult MSDS for further precautions and handling advice.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product. **Date: 07/06/2010**