

ThixoCal™ 5752B

Formulated Rust & Corrosion Preventive Compound

ThixoCal™ 5752B is a specially formulated corrosion preventive compound with enhanced penetrating characteristics. ThixoCal™ 5752B is comprised of gelled calcium sulfonate, waxes, oils, and other special ingredients in a mineral spirits carrier. This product offers excellent underbody protection to vehicles exposed to highway deicing salts. This product will provide somewhat tacky films with excellent salt spray protection.

ThixoCal™ 5752B is a general rust proofing compound that may be used for both underbody and inner panel cavity protection. This product is also an excellent choice for temporary or long-term protection of metal parts and tubular goods during transit and indoor/ outdoor storage.

ThixoCal™ 5752B is also a good choice for temporary or prolonged protection of metal goods including premium applications such as protection of railroad equipment and electronic communications equipment including support vehicles and structures.

TECHNICAL PROPERTIES *(not specifications):*

<u>PROPERTY</u>	<u>ASTM</u>	<u>TYPICAL</u>
Non-volatiles, Wt%	D2369	52 - 56
Brookfield Viscosity, cP	D2196	3 - 6000
Flash Point °F, min.	D93	105
Lbs/ Gal. @ 25°C	D1475	Report
Salt Spray Test, 3.0 mils dry film thickness (DFT), min. hours	B117-85	2,000

AVAILABILITY

ThixoCal™ 5752B is available in drums and bulk.

SAFETY, HANDLING AND STORAGE

ThixoCal™ 5752B contains mineral spirits and should be stored away from heat, flame and sources of ignition. Prolonged breathing of vapors should be avoided. Consult MSDS for further precautions and handling advice.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.

Date: 07/06/2010